

UPM Raflatac Technical Information

01.22.2014 AME 1871

Product	VOID TEXT WHITE TC RC18 2.2 mil HIGH DENSITY WHITE		
Sales Code	SP056K		
Description	VOID TEXT WHITE TC RC18 2.2 mil HIGH DENSITY WHITE		
Substance weight	111 lbs./ream (25" x 38")		
Caliper	4.8 mil		
Face	VOID TEXT WHITE TC		
Product	White, matte top-coated polyester security film.		
Use	Film splits leaving 'void' text pattern when removed. Product is designed for conventional printing methods and thermal transfer with selected ribbons.		
Substance weight	lbs/ream		
	50	(25in x 38in)	TAPPI-410
Caliper	2.10	mil	TAPPI-411
Adhesive	RC18		
Type	Permanent adhesive.		
Composition	Radiation-cured UV acrylic.		
Use	Designed specifically for film face materials for end-uses where very good adhesion with good chemical and temperature resistance is needed.		
Tack	15.0	N	FTM 9
Minimum labelling temperature	41	°F	
Service temperature minimum	14	°F	
Service temperature maximum	248	°F	
Shelf life	From the date of manufacture: 2 years at 68°F and RH 50%.		
Liner	2.2 mil HIGH DENSITY WHITE		
Product	White high density liner.		
Use	Specially developed for filmic label material giving the best conversion properties. Good with photocells dispensing systems.		
Substance weight	lbs/ream		
	39	(24in x 36in)	TAPPI-410
Caliper	2.20	mil	TAPPI-411
Tensile strength MD	46	lbf/in	TAPPI-494
Tensile strength CD	20	lbf/in	TAPPI-494
Opacity	54	%	TAPPI-425


UPM
www.upmraflatac.com

Disclaimer The above are typical technical values and are given in good faith based upon our most up to date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused using the product. Our technical product consulting experts are on standby to provide you with targeted support. Contact a member of our team toll-free at 1-866-294-8412.



UPM

www.upmraflatac.com